



Project _____ City _____ State _____ Bid Date _____

 Airport
 Correctional
 Educational
 Parking Garage
 Retirement Center
 Security
 Other
SYSTEM COMPONENTS

Model	Description	Quantity	Price	Total
VS-900MF	Exchange mainframe, supports up to (4) MS-900 master stations or telephone masters and (64) RS Series sub-stations, slots for (2) VS-900MS/VS-900AL, (4) VS-900RS, (1) VS-900CO, (1) VS-900AF, (1) VS-900TI, requires (1) PU-200 for (1-32) sub-stations and (2) PU-200 for (33-64) sub-stations, rack-mount kit included (10 RU), optional wall-mount bracket (YC-303)			
YC-303	Wall-mount bracket for VS-900MF			
PU-200	Power supply for VS-900MF, each mainframe uses (1) PU-200 for (1-32) sub-stations and (2) PU-200 for (33-64) sub-stations, wall-mount brackets included, optional rack-mount panel (PN-100B)			
PN-100B	Rack-mount panel (4 RU) for (2) PU-200			
VS-900MS	Master station line card, supports (2) MS-900, individual record outputs w/control activation, removable terminal blocks			
VS-900AL	Telephone master station line card, supports (2) analog telephones w/caller ID signaling, individual record outputs w/control activation, removable terminal blocks			
VS-900RS	Sub-station line card, 16 ports, supports (16) RS-150, RS-160, RS-170 or RS-180, (2) speech links, removable terminal blocks (external amplifier required for station paging)			
VS-910RS	Four-Wire Sub-station Line Card, supports (16) RS-190			
VS-900CO	C/O Telephone line interface card, supports (2) outside telephone (C/O) lines, individual record outputs w/control activation, removable terminal blocks			
VS-900AF	Audio function card, (1) paging line output w/ (16) control outputs, (1) external source line input w/ (4) trigger inputs, (1) conference link, removable terminal blocks			
VS-900TI	Tie-line interface card, required in each exchange in a multi-exchange system (16 max.), (4) speech paths, (1) data link, removable terminal blocks			
VS-900SC	Site connector tie-line interface, for remote tie-lined exchange locations, allows standard media converters (fiber, etc.), required in multi-exchange systems w/ (3) or more exchanges, combines four voice links from two VS-900TI, rack-mount kit included (2 RU), requires PU-200 power supply			

STATION EQUIPMENT

MS-900	Desktop Master Station			
XWJ-100F	Flush-Mount Modular Jack for MS-900 or Telephone Master Station			
XWJ-100S	Surface-Mount Modular Jack for MS-900 or Telephone Master Station			
RS-150	Economy Indoor Sub-station			
RS-160	Indoor Sub-station			
RS-170	Outdoor Sub-station			
RS-180	Panic Sub-station, contact output			
RS-190	Four-Wire Indoor Sub-station			
RS-191	Optional Four-Wire Handset for RS-190			

PERIPHERALS

VS-900DI	Direct Select/Master Station Interface Card			
VS-910DI	Direct Select I/O Card			
XPS-24VS	Power Supply Supports (1) VS-900DI and (2) VS-910DI			

Dealer _____

Suggested Total \$ _____

City _____ State _____