

EABOX QAM

TOALERT Dynamic View



Dynamic View is a smart media player that allows you to display EverAlert platform alerts, messages, and communications on a broad range of large-format TV monitors through HDMI input. With the ability to broadcast on larger screens, organizations can more clearly communicate daily messages, precise synchronized time, and emergency alerts such as severe weather, lockdown protocols, fire drills, and more.

Key features

- Communicates to the TOAlert ManagementPortal through wired Ethernet or Wi-Fi network
- HDMI connection to TV/monitors
- Supports HD, large-format resolutions

Specifications

Power Source	100 - 240 V AC, 50/60Hz
Output Voltage	12 V DC
Power Consumption	9.5W (average), 14.5W (maximum)
Resolution	1920 x 1080
Display Format	Landscape (horizontal)
USB Port	2
External Speaker Terminal	3.5 mm
Wired LAN Connectivity	10/100M, RJ45 connector
Wireless LAN Connectivity	802.11b/g/n (2.4GHz)
USB Provisioning	USB drive with AES encryption
Wired Provisioning	LAN/DHCP Web portal on network connection
Time Synchronization Support	2 static IP address time servers or pool SNTP domain name
Clock Battery Backup for Power Outages	CR1220 lithium
Compliance/Certifications	ROHS, CE/FCC, PSU with UL
Operating Humidity	85% maximum, non-condensting
Operating Temperature	0 °C - 40 °C
Dimensions	7.5"L x 3.75"H x .75"W (device only)
Weight	1.1 lbs

A&E specifications

The dynamic view shall display communications on a broad range of large format screens through and connect via HDMI output. The smart media player, when connected to the TOAlert platform, allows the display of emergency alerts, daily messages and synchronizes time on the TV displays. The system shall have the capability to display information in three formats; English, French, and both simultaneously. The device shall include the preloaded operating system software. The dynamic view shall communicate with the TOAlert management portal through wired Ethernet or Wi-Fi network. The device comes with a 2-year warranty. The dynamic view is sold as part of the TOAlert system and is covered under the 5-year license for operation within the communication platform. The device shall have 2 USB ports and a 3.5mm output for an external speaker connection. Input voltage to power supply 100-240VAC, 50/60Hz and output voltage from power supply 12VDC. Power consumption 9.5W (average), 14.5W (maximum). The dimension of the display device shall be 11.25" L x 9.25" W x 3" H x (285.7 L x 235 W x 76.2 H mm). Weight shall be 2.6 lbs. The Dynamic View shall be TOA model EABOX