

Q-SC-P620

POWERED HORN SPEAKER



The Q-SC-P620 is a highly intelligible and compact horn speaker with a built-in 20W digital power amplifier, that provides public address announcement and remote paging for network video surveillance applications. This powered horn speaker can operate at extreme temperatures. It comes with powder-coated finish and stainless-steel screws to ensure its weatherproof capability. Ideal choice for indoor and outdoor applications in train stations, airports and many more.

Key features

- Integrated 20W power amplifier which utilizes latest Class D technology
- Switchable Gain: 8dB, 16dB, 24dB and 32dB
- Internal volume control to allow on-site tuning
- Integration to CCTV systems possible with the majority of IP CCTV systems equipped with an audio line output
- Weatherproof to IP65 rating

Specifications

Power Source	12V DC, 2A (DC Socket "+" Type A : 5.5 x 2.1mm)
Power Consumption	15W (1.25A) at Rated output , 25W (2.1 OA) at Maximum output
Input	0 dB*, 1 Ok 0, Unbalanced (RCA plug)
Signal Gain	8, 16, 24 or 32db (Factory pre-set to 16db)
Volume Adjustment	Internal volume control (Factory pre-set to maximum position)
Sound Pressure Level	113dB (1 W, 1 m at 500Hz to 2.5KHz peak level) Max. SPL (above 120dB)
Frequency Response	250 - 10,000 Hz
Dust/Water Protection	IP 65
Finish	Horn Flare: HIPS resin, white (RAL9010 equivalent) Reflector horn and case: ABS resin, white (RAL9010 equivalent) Bracket, screws & bolts: Stainless steel
Dimensions	292 (W) x 230 (H) x 280 (D) mm
Weight	1.8 kg
Optional Accessories	AD-5000-2 (LTE24E-S2-1) AC Adapter

Dimensions

